

i2Share

2024.05.12 16:59:08

FAQ

标题:	i2Share FAQ	浏览次数:	0
作者:	()	浏览量:	0.00 %
语言:	zh_CN	最后更新:	2023/09/27 14:58:33

()

()

()

```
1.  i2Share /data/i2share/webhub_settings.py
   AUTO_FILE_SERVER_ROOT_PATH = 'filehttp'
   i2share-admin stop
   i2share-admin start

2.  nginx /etc/nginx/conf.d/i2share.conf
   server 8000
   nginx -s reload

3.  debug
   map $host $the_port {
       default $http_x_forwarded_port;
       "106.41.69.46" "8000";
   }

   gzip on; #Gzip
   gzip_min_length 1k; #1K
   gzip_comp_level 3; #1-10
   gzip_types text/plain application/javascript application/x-javascript text/css
   application/xml text/javascript application/x-httpd-php image/gif image/png;
   #.jpg
   gzip_vary on;
   gzip_disable "MSIE [1-6]\.";
   map $http_x_forwarded_proto $the_scheme {
       default $http_x_forwarded_proto;
       "" $scheme;
   }
   map $http_x_forwarded_host $the_host {
       default $http_x_forwarded_host;
       "" $host;
   }
   map $http_upgrade $proxy_connection {
       default upgrade;
       "" close;
   }
   map $http_x_forwarded_port $the_port {
       default $http_x_forwarded_port;
       "" $server_port;
   }
   map $host $the_port {
       default $http_x_forwarded_port;
       "106.41.69.46" "8000";
   }
   server {
       listen 80;
       server_name 192.168.0.8; # $I2SHARE_SERVER_IP_OR_DOMAIN IP
       server_tokens off;
       proxy_set_header X-Forwarded-For $remote_addr;
       if ($request_method !~* GET|POST|PUT|DELETE|HEAD) {
           return 405;
       }
       set $lang $http_accept_language;
       if ($http_accept_language ~* ^zh-Hant){
           set $lang "zh-Hant";
       }
       location / {
           proxy_pass http://127.0.0.1:8000;
           proxy_set_header Host $http_host;
           proxy_set_header X-Real-IP $remote_addr;
           proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
           proxy_set_header X-Forwarded-Host $the_host;
           proxy_set_header X-Forwarded-Port $the_port;
           proxy_set_header X-Forwarded-Proto $the_scheme;
           proxy_set_header Accept-Language $lang;
           proxy_read_timeout 1200s;
           # used for view/edit office file via Office Online Server
           client_max_body_size 0;
       }
   }
```

```

access_log    /var/log/nginx/i2share.access.log;
error_log     /var/log/nginx/i2share.error.log;
}
location /filehttp {
    rewrite ^/filehttp(.*)$ $1 break;
    proxy_pass http://127.0.0.1:8082;
    client_max_body_size 0;
    proxy_connect_timeout 36000s;
    proxy_read_timeout 36000s;
    proxy_max_temp_file_size 0;
    proxy_buffering off;
}
location /media {
    root /data/i2share/i2share-server/websvr;
}
location /frontend {
    root /data/i2share/i2share-server/websvr;
}
# onlyoffice onlyofficeURL
#location /onlyofficedocs/ {
# # THIS ONE IS IMPORTANT ! - Trailing slash !
# #
# proxy_pass $ONLYOFFICE_SERVICE_URL;
# $ONLYOFFICE_SERVICE_URLonlyofficeURLURL""/""
# proxy_http_version 1.1;
# client_max_body_size 100M; # 100M
# proxy_read_timeout 3600s;
# proxy_connect_timeout 3600s;
# proxy_set_header Upgrade $http_upgrade;
# proxy_set_header Connection $proxy_connection;
# # THIS ONE IS IMPORTANT ! - Subfolder and NO trailing slash !
# proxy_set_header X-Forwarded-Host $the_host/onlyofficedocs;
# proxy_set_header X-Forwarded-Proto $the_scheme;
# proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
#}
# webdav
#location /i2sharedav {
# proxy_pass http://127.0.0.1:8080;
# proxy_set_header Host $http_host;
# proxy_set_header X-Real-IP $remote_addr;
# proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
# proxy_set_header X-Forwarded-Host $the_host;
# proxy_set_header X-Forwarded-Port $the_port;
# proxy_set_header X-Forwarded-Proto $scheme;
# proxy_set_header Accept-Language $lang;
# proxy_read_timeout 1200s;
# client_max_body_size 0;
# proxy_max_temp_file_size 0;
# proxy_buffering off;
# access_log /var/log/nginx/i2share.webdav.access.log;
# error_log /var/log/nginx/i2share.webdav.error.log;
#}
}
server {
    listen 800;
    server_name 106.41.69.46; #
    $I2SHARE_SERVER_IP_OR_DOMAINIP
    server_tokens off;
    proxy_set_header X-Forwarded-For $remote_addr;
    if ($request_method !~* GET|POST|PUT|DELETE|HEAD) {
        return 405;
    }
    set $lang $http_accept_language;
    if ($http_accept_language ~* ^zh-Hant){
        set $lang "zh-Hant";
    }
    location / {
        proxy_pass http://127.0.0.1:8000;
        proxy_set_header Host $http_host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Host $the_host;
        proxy_set_header X-Forwarded-Port $the_port;
        proxy_set_header X-Forwarded-Proto $the_scheme;
        proxy_set_header Accept-Language $lang;
        proxy_read_timeout 1200s;
        # used for view/edit office file via Office Online Server
        client_max_body_size 0;
        access_log /var/log/nginx/i2share.access.log;
        error_log /var/log/nginx/i2share.error.log;
    }
    location /filehttp {
        rewrite ^/filehttp(.*)$ $1 break;
        proxy_pass http://127.0.0.1:8082;
        client_max_body_size 0;
        proxy_connect_timeout 36000s;
        proxy_read_timeout 36000s;
        proxy_max_temp_file_size 0;
        proxy_buffering off;
    }
    location /media {
        root /data/i2share/i2share-server/websvr;
    }
    location /frontend {
        root /data/i2share/i2share-server/websvr;
    }
    # onlyoffice onlyofficeURL
    #location /onlyofficedocs/ {
    # # THIS ONE IS IMPORTANT ! - Trailing slash !
    # #
    # proxy_pass $ONLYOFFICE_SERVICE_URL;
    # $ONLYOFFICE_SERVICE_URLonlyofficeURLURL""/""

```

```
# proxy_http_version 1.1;
# client_max_body_size 100M; # 100M
# proxy_read_timeout 3600s;
# proxy_connect_timeout 3600s;
# proxy_set_header Upgrade $http_upgrade;
# proxy_set_header Connection $proxy_connection;
# # THIS ONE IS IMPORTANT ! - Subfolder and NO trailing slash !
# proxy_set_header X-Forwarded-Host $the_host/onlyofficed;
# proxy_set_header X-Forwarded-Proto $the_scheme;
# proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
#}
# 1000webdav10000000
#location /i2share {
# proxy_pass http://127.0.0.1:8080;
# proxy_set_header Host $http_host;
# proxy_set_header X-Real-IP $remote_addr;
# proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
# proxy_set_header X-Forwarded-Host $the_host;
# proxy_set_header X-Forwarded-Port $the_port;
# proxy_set_header X-Forwarded-Proto $scheme;
# proxy_set_header Accept-Language $lang;
# proxy_read_timeout 1200s;
# client_max_body_size 0;
# proxy_max_temp_file_size 0;
# proxy_buffering off;
# access_log /var/log/nginx/i2share.webdav.access.log;
# error_log /var/log/nginx/i2share.webdav.error.log;
#}
}
```